

LG1000 Powered by Cummins

Model	Frequency/RPM	Standby Power	Prime Power
LG1000P	50Hz/1500RPM	800KW	720KW
		1000KVA	900KVA

* Voltages: 230/400V


- (1) Prime Power: Ratings are as per DIN 6271, BS55114 and ISO-3046 with 10% overload capacity.
- (2) Standby Power: Power available at variable load for up to a max. of 500 hours during one year of which 300 hours may be for continuous use.
- (3) Operation at Altitude \leq 1000m, Ambient temperature \leq 40°C. If altitude higher than 1000m, each 300m will cause additional de-rating 4%.

General Characteristics

Model	LG1000P
Engine	Perkins 4008TAG1A
Alternator	Stamford or Lega
Speed Control Type	Electrical
Phase	3
System Voltage	24
Frequency	50Hz
Engine Sped(RPM)	1500
Controller Model	AMF IntelliLite 9 or DEEPPSEA DSE6020)

Dimensions

DIMENSION	OPEN TYPE	SILENT TYPE
Length (L)	4700mm	6170mm
Width (W)	2060mm	2390mm
Height (H)	2360mm	2632mm
Net Weight (KG)	7300KG	12300KG



Engine Specification

Brand	Perkins	
Model	4008TAG1A	
No. of Cylinders and Cycle	8L, 4 Stroke	
Compression Ratio	13.6:1	
Displacement (L)	30.561	
Bore x Stroke (mm)	160 x 190	
Piston Speed (m/s)	9.5	
Air Intake Flow (L/s)	1156.67	
Exhaust Flow (L/s)	3050	
Net Engine Weight (kg)	4270	
Starting System	Electronic	
Engine Coolant Flow (L/s)	10	
Base Output Power (kW)	805	
Fuel Consumption (L/h)	110% load	218
	100% load	195
	75% load	143
	50% load	98

Cooling System	Max.coolant cycling resistance exterior engine(kPA)	20
	Thermostat adjusting temperature (°C)	71-85
	Minimum Pressure of Radiator Cap (kPA)	69
	Coolant capacity-engine only(L)	48
Fuel System	Fuel injection pump model	Direct injection
	Maximum Fuel Inlet Temperature (°C)	58
Lubricating System	Max. oil temperature permitted in oil pan (°C)	105
	Lubrication system Min. capacity (L)	127
Exhaust System	Max. Back Pressure (kPA)	3
Electrical System	Starter (V)	24
	Battery charging system (A)	40

Alternator Specification

Poles	No.	4
Connection type (standard)		VOLTAGE STAR
Insulation		Class" H"
Enclosure (according IEC-34-5)		IP23
Exciter system		PMG
Voltage regulator		A.V.R. (Electronic)
Bracket type		Single bearing
Coupling system		Flexible disc
Coating type		Standard (Vacuum impregnation)

*Alternator meets BS EN 60034 and the relevant section of other international standards such as BS5000, VDE 0530, NEMA MG1-32, IEC34, CSA C22.2 and AS1359.

Options

Engine

- Jacket Water Preheater
- Oil Preheater

Generator Sets

- Tools with the machine

Fuel System

- Low fuel level alarm
- Automatic fuel feeding system
- Fuel T-valves

Control Panel

- Remote control panel
- ATS
- Remote controller
- Synchronizing controller

Alternator

- Winding temperature measuring instrument
- Alternator Preheater
- Anti-damp and anti-corrosion treatment
- Anti-condensation heater

Canopy

- Rental type canopy
- Trailer

Exhaust System

- Protection board from heat

Cooling System

- Front heat protection
- Coolant (-30°C)

Lubricating System

- With machine oil

Note: This drawing is provided for reference only and should not be used for planning installation. Contact your




Control	Auto/Start/Stop Control Emergency Stop Pushbutton/ Alarm Engine Cool Down Timer Warm - up Timer Load Switching Timer Engine Cycle Crank	
Indications	Operating Hours 3 Phase Generator Voltage Sensing & Monitoring Current Protection & Monitoring Power Measurement (kW, kVA, kVAR, kWh, kVAh, pf) Frequency Monitoring (Hz) Oil Pressure/Coolant Temperature/Fuel Level Monitoring Battery Voltage Monitoring (DC) Alarm (Acknowledge)	AMF IntelliLite 9
Warning & Shutdown Alarms	Generator Over/Under Voltage & Frequency Crank Disconnect (Failure to Start) Under/Over Speed Over Current Low oil pressure High Water Temperature Low Fuel Level Low Water Level	 DSE6020
Features	IP 65 (if ordered with gasket) Basic Scheduler 8 - 35V DC Supply Digital Inputs(4) - Outputs(4 MPU/ 6 CAN) Event Log (5 shutdowns)	

All data is subject to change without notice. Sorry for inform.



We are always Available

Distributed By:



Fujian Everstrong Lega Power Equipments Co., Ltd
 Fuqing Hong Kuan Industry Zone, Fuzhou, Fujian
 Province, China
 Tel: +86-591-8385 3032
 Fax: +86-591-8385 3130
 Email: sales@legapower.com
 Web: www.legapower.com