



# LG2030 Powered by Cummins

Model	Frequency/RPM	Standby Power	Prime Power
LG2030P	50Hz/1500RPM	1624KW	1480KW
		2030KVA	1850KVA

\* Voltages: 230/400V


- (1) Prime Power: Ratings are as per DIN 6271, BS55114 and ISO-3046 with 10% overload capacity.
- (2) Standby Power: Power available at variable load for up to a max. of 500 hours during one year of which 300 hours may be for continuous use
- (3) Operation at Altitude  $\leq$  1000m, Ambient temperature  $\leq$  40°C. If altitude higher than 1000m, each 300m will cause additional de-rating 4%.

## General Characteristics

Model	LG2030P
Engine	Perkins 4016TAG1A
Alternator	STAMFORD
Speed Control Type	Electrical
Phase	3
System Voltage	24
Frequency	50Hz
Engine Sped(RPM)	1500
Controller Model	AMF IntelliLite 9 or DEEPSEA DSE6020)

## Dimensions

DIMENSION	OPEN TYPE	SILENT TYPE
Length (L)	6000mm	2450mm
Width (W)	2170mm	1080mm
Height (H)	2740mm	1865mm
Net Weight (KG)	11000KG	1350KG



### Engine Specification

Brand	Perkins	
Model	4016TAG1A	
No. of Cylinders and Cycle	16V, 4 Stroke	
Compression Ratio	13.6:1	
Displacement (L)	61.123	
Bore x Stroke (mm)	160 x 190	
Piston Speed (m/s)	9.5	
Air Intake Flow (L/s)	2200	
Exhaust Flow (L/s)	5716.67	
Net Engine Weight (kg)	5570	
Starting System	Electronic	
Engine Coolant Flow (L/s)	17.02	
Base Output Power (kW)	1588	
Fuel Consumption (L/h)	110% load	424
	100% load	383
	75% load	277
	50% load	185

Cooling System	Thermostat adjusting temperature (°C )	71-85
	Minimum Pressure of Radiator Cap (kPA)	69
	Coolant capacity-engine only(L)	95
Fuel System	Fuel injection pump model	Direct i
	Maximum Fuel Inlet Temperature (°C )	58
Lubricating System	Low idle (kPA)	340
	Max. oil temperature permitted in oil pan (°C )	105
	Lubrication system Min. capacity (L)	147
Electrical System	Starter (V)	24
	Battery charging system (A)	55

### Alternator Specification

Poles	No	4
-------	----	---

Connection type (standard)		Star
Insulation	⊗	Class" H"
Enclosure (according IEC-34-5)		IP23
Exciter system		PMG
Voltage regulator		A.V.R. (Electronic)
Bracket type	⊗	Single bearing
Coupling system		Flexible disc
Coating type		Standard (Vacuum impregnati

\*Alternator meets BS EN 60034 and the relevant section of other international standards such as BS5000, VDE 0530, NEMA MG1-32, IEC34, C: AS1359.

## Options

### Engine

- Jacket Water Preheater
- Oil Preheater

### Generator Sets

- Tools with the machine

### Fuel System

- Low fuel level alarm
- Automatic fuel feeding system
- Fuel T-valves

### Control Panel

- Remote control panel
- ATS
- Remote controller
- Synchronizing controller

### Alternator

- Winding temperature measuring instrumer
- Alternator Preheater
- Anti-damp and anti-corrosion treatment
- Anti-condensation heater

### Canopy

- Rental type canopy
- Trailer

### Exhaust System

- Protection board from heat

### Cooling System

- Front heat protection
- Coolant (-30°C)



### Lubricating System

- With machine oil

Note: This drawing is provided for reference only and should not be used for planning installation. Contact yc



Standard Controller (ComAp AMF20 or DEEPSEA DSE6020)

Control	Emergency Stop Pushbutton/ Alarm Engine Cool Down Timer Warm - up Timer Load Switching Timer Engine Cycle Crank	
Indications	Operating Hours 3 Phase Generator Voltage Sensing & Monitoring Current Protection & Monitoring Power Measurement (kW, kVA, kVAr, kWh, kVAh, pf) Frequency Monitoring (Hz) Oil Pressure/Coolant Temperature/Fuel Level Monitoring Battery Voltage Monitoring (DC) Alarm (Acknowledge)	AMF Intelli
Warning & Shutdown Alarms	Generator Over/Under Voltage & Frequency Crank Disconnect (Failure to Start) Under/Over Speed Over Current Low oil pressure High Water Temperature Low Fuel Level Low Water Level	 DSE6020
Features	IP 65 (if ordered with gasket) Basic Scheduler 8 - 35V DC Supply Digital Inputs(4) - Outputs(4 MPU/ 6 CAN) Event Log (5 shutdowns)	

All data is subject to change without notice. Sorry for inform.

Distributed By:



Fujian Everstrong Lega Power Equipmer  
 Fuqing Hong Kuan Industry Zone, Fuzh  
 Provi  
 Tel: +86-591-  
 Fax: +86-591-  
 Email: sales@legap  
 Web: www.legap



CE

wer


--

--

--

--

--



--

YPE

--

--

--



CE



\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Injection

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

CE



\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

ion)  
SA C22.2 and



it

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

\_\_\_\_\_


our local

CE





Lite 9



always  
**reliable**

ComAp  
Energy Co., Ltd  
Zhouzhen, Fujian  
Province, China  
Tel: +86 592 8385 3032  
Tel: +86 592 8385 3130  
www.comap.com  
comap.com