



# LG1650C Powered by Cummins

Model	Frequency/RPM	Standby Power	Prime Power
LG1650C	50Hz/1500RPM	1320KW	N.A.
		1650KVA	N.A.

\* Voltage: 400/230


- (1) Prime Power: Ratings are as per DIN 6271, BS55114 and ISO-3046 with 10% overload capacity.
- (2) Standby Power: Power available at variable load for up to a max. of 500 hours during one year of which 300 hours may be for continuous use.
- (3) Operation at Altitude  $\leq$  1000m, Ambient temperature  $\leq$  40°C. If altitude higher than 1000m, each 300m will cause additional de-rating 4%.

## General Characteristics

Model	LG1650C
Engine	Cummins KTA50G8
Alternator	Stamford or Lega
Speed Control Type	Electrical
Phase	3
System Voltage	24
Frequency	50Hz
Engine Sped(RPM)	1500

## Dimensions

DIMENSION	OPEN TYPE	SILENT TYPE
Length (L)	4470mm	
Width (W)	2170mm	
Height (H)	2240mm	
Net Weight (KG)	7650kg	



Engine Specification		
Brand	Cummins	
Model	KTA50G8	
No. of Cylinders and Cycle	16V, 4 Stroke	
Compression Ratio	14.9:1	
Displacement (L)	50.3	
Bore x Stroke (mm)	159 x 159	
Piston Speed (m/s)	7.9	
Air Intake Flow (L/s)	1500	
Exhaust Flow (L/s)	3845	
Net Engine Weight (kg)	5360	
Starting System	Electronic	
Engine Coolant Flow (L/min)	27.8	
Base Output Power (kW)	1200	
Fuel Consumption (L/h)	100% load	289
	75% load	222
	50% load	155
	25% load	82
Cooling System	Max.coolant cycling resistance exterior engine(kPA)	67
	Thermostat adjusting temperature (°C )	82-93
	Minimum Pressure of Radiator Cap (kPA)	67
	Coolant capacity-engine only(L)	165
Fuel System	Fuel injection pump model	Direct Injection Cummins PT
	Maximum Restriction at Lift Pump (kPa)	13.3
	Total Drain Flow (constant for all loads) (L/h)	570
Lubricating System	Low idle (kPA)	138
	Rated speed (kPA)	345-483
	Max. oil temperature permitted in oil pan (°C )	121
	Lubrication system Min. capacity (L)	204
Exhaust System	Max. Back Pressure (kPA)	6.7
Electrical System	Starter (V)	24
	Battery charging system (A)	35

## Alternator Specification

Poles	No.	4
Connection type (standard)		star
Insulation		Class" H"
Enclosure (according IEC-34-5)		IP23
Exciter system		PMG
Voltage regulator		A.V.R. (Electronic)
Bracket type		Single bearing
Coupling system		Flexible disc
Coating type		Standard (Vacuum impregnation)

\*Alternator meets BS EN 60034 and the relevant section of other international standards such as BS5000, VDE 0530, NEMA MG1-32, IEC34, CSA C22.2 and AS1359.

## Options

### Engine

- Jacket Water Preheater
- Oil Preheater

### Generator Sets

- Tools with the machine

### Fuel System

- Low fuel level alarm
- Automatic fuel feeding system
- Fuel T-valves

### Control Panel

- Remote control panel
- ATS
- Remote controller
- Synchronizing controller

### Alternator

- Winding temperature measuring instrument
- Alternator Preheater
- Anti-damp and anti-corrosion treatment
- Anti-condensation heater

### Canopy

- Rental type canopy
- Trailer

### Exhaust System

- Protection board from heat

### Cooling System

- Front heat protection
- Coolant (-30°C)

### Lubricating System

- With machine oil

Note: This drawing is provided for reference only and should not be used for planning installation. Contact your

Standard Controller (ComAp AMF20 or DEEPSEA DSE6020)

Control	<ul style="list-style-type: none"> <li>Auto/Start/Stop Control</li> <li>Emergency Stop Pushbutton/ Alarm</li> <li>Engine Cool Down Timer</li> <li>Warm - up Timer</li> <li>Load Switching Timer</li> <li>Engine Cycle Crank</li> </ul>	
Indications	<ul style="list-style-type: none"> <li>Operating Hours</li> <li>3 Phase Generator Voltage Sensing &amp; Monitoring</li> <li>Current Protection &amp; Monitoring</li> <li>Power Measurement (kW, kVA, kVA<sub>r</sub>, kWh, kVA<sub>h</sub>, pf)</li> <li>Frequency Monitoring (Hz)</li> <li>Oil Pressure/Coolant Temperature/Fuel Level Monitoring</li> <li>Battery Voltage Monitoring (DC)</li> <li>Alarm (Acknowledge)</li> </ul>	AMF IntelliLite 9
Warning & Shutdown Alarms	<ul style="list-style-type: none"> <li>Generator Over/Under Voltage &amp; Frequency</li> <li>Crank Disconnect (Failure to Start)</li> <li>Under/Over Speed</li> <li>Over Current</li> <li>Low oil pressure</li> <li>High Water Temperature</li> <li>Low Fuel Level</li> <li>Low Water Level</li> </ul>	
Features	<ul style="list-style-type: none"> <li>IP 65 (if ordered with gasket)</li> <li>Basic Scheduler</li> <li>8 - 35V DC Supply</li> <li>Digital Inputs(4) - Outputs(4 MPU/ 6 CAN)</li> <li>Event Log (5 shutdowns)</li> </ul>	DSE6020

All data is subject to change without notice. Sorry for inform.



Distributed By:

Fujian Everstrong Lega Power Equipments Co., Ltd  
 Fuqing Hong Kuan Industry Zone, Fuzhou, Fujian  
 Province, China  
 Tel: +86-591-8385 3032  
 Fax: +86-591-8385 3130  
 Email: sales@legapower.com  
 Web: www.legapower.com