

EPF-32 Series Fuse Holder and Links

Technical data

Standard	IEC 60947-3
Description	Fuse switch disconnecter with LED indicator
Number of Poles	1P,2P,3P,4P
Fuse size	10X38
Rated operational current Ie	2-32A
Rated operational voltage Ue	250VAC(1P)/500VAC(2P-4P)
Rated insulation voltage	500VAC
Rated impulse withstand voltage	4kV
Conditional short-circuit current	20kA
Utilization category with fuse	g G
Protection degree	IP20
Mounting method	Din rail installation



CE CB



EPF-32-1P



EPF-32-2P







EPF-32-3P



EPF-32-4P

EPF-32 Fuse Holder and Links

	Code No.	Fuse link size	Link current	Packing unit (holder)	Packing unit(link)
 <p>EPF-32-1P</p>	EPF-32-1 EPF-32X-1	10 X 38mm	2A	12	200
			4A	12	200
			6A	12	200
			10A	12	200
			16A	12	200
			20A	12	200
			25A	12	200
			32A	12	200
 <p>EPF-32-2P</p>	EPF-32-2 EPF-32X-2	10 X 38mm	2A	6	200
			4A	6	200
			6A	6	200
			10A	6	200
			16A	6	200
			20A	6	200
			25A	6	200
			32A	6	200
 <p>EPF-32-3P</p>	EPF-32-3 EPF-32X-3	10 X 38mm	2A	4	200
			4A	4	200
			6A	4	200
			10A	4	200
			16A	4	200
			20A	4	200
			25A	4	200
			32A	4	200
 <p>EPF-32-4P</p>	EPF-32-4 EPF-32X-4	10 X 38mm	2A	3	200
			4A	3	200
			6A	3	200
			10A	3	200
			16A	3	200
			20A	3	200
			25A	3	200
			32A	3	200