

LE209C综合智能售货机+冷/热现磨咖啡机





整机参数 The Whole Machine Parameter

● 产品型号 Model No.	LE209C
● 产品尺寸 Machine Size	(高)1930mm*(深)900mm* (宽)1460mm
● 重量 Net Weight	≈385kg(including water chiller含冰水机)
● 用电参数 Rated Voltage	AC220-240V、50-60Hz 或者 110~120V/60Hz; 整机功率2250W,待机功率:80W AC220-240V, 50-60Hz or AC 110~120V/60Hz; Rated power: 2250W, Standby power: 80W
● 显示屏 Display Screen	21.5英寸10点触摸, RGB全彩色, 分辨率1920*1080MAX 21.5 inches, Multi-finger touch (10 finger), RGB full color, Resolution: 1920*1080MAX
● 通讯接口 Communication Interface	RS232串口3个, 4个USB2.0 Host, 1个HDMI 2.0 Three RS232 Serial port , 4 USB2.0Host, one Ethernet port
● 操作系统 Operation System	Android7.1
● 联网方式 Internet Supported	3G,4G Sim card, WIFI, Ethernet port 物联网卡3G,4G全网通、WIFI、千兆以太网端口
● 支付方式 Payment Type	现金, 手机二维码, 银行卡刷卡器, ID刷卡, 扫码枪等 Cash, Mobile QR code, bank card, ID card, Barcode scanner,etc
● 大门锁 Door Lock	机械锁 Mechanical Lock
● Water Supply Mode 供水方式	下抽水, 桶装纯净水 (19L*2桶) By water pumping, Bottled Purified water (19L*2 bottles)
● 杯子容量 Cup Capacity	5桶落杯, 每桶30个, 杯子规格: 口径ø90 12盎司 150pcs, cup size ø90, 12ounce
● 杯盖容量 Cup lid Capacity	单桶落盖, 存储量为100pcs
● 水箱容量 Built-in Water Tank Capacity	1.5L
● 豆仓、料盒容量 Coffee Bean House Capacity	1个豆仓: 6L(约2kg) ; 5个粉料盒: 4L (约1.5kg) One coffee bean house: 6L (About 2kg); 5 canisters, 4L each (about 1.5kg)
● 管理后台 Management System	PC端+移动端云平台管理 PC terminal + mobile terminal PTZ management
● 功能检测 Detection Function	无水报警、无杯报警、无豆报警 Alert when out of water, cups or beans
● 废渣桶容量 Dry Waste Capacity	15L (300个咖啡饼)
● 废水桶容量 Waste Water Tank Capacity	12L
● 取杯方式 Cup Door	取杯门自动开合 Open automatically after drinks ready
● 取盖方式 Cup lid Door	取盖门手动开合 Slide up and down manually
● 灭菌系统 Sterilization System	紫外线杀菌 (空气) , UV杀菌 (水源) Time-controlled UV lamp for air, UV lamp for water
● 使用环境 Application Environment	室内使用, 相对湿度≤ 90%RH, 环境温度≤40°C, 海拔高度≤1000m Relative Humidity ≤ 90%RH, Environment Temperature: 4-38°C, Altitude≤1000m
● 视频播放 AD Video	有 YES
● 灯箱广告 AD Light lamp	有 YES

LE209C 冰水机参数 Water Chiller Parameter

● 产品尺寸 Machine Size	(H) 650* (D) 266* (W) 300mm
● 重量 Net Weight	≈20Kg
● 电参数 Rated Voltage	AC220-240V, 频率50Hz,整机功率400W, 待机功率10W AC220-240V, 50Hz or AC 110~120V/60Hz; Rated power: 400W, Standby power: 10W
● 制冷方式 Cooling Method	压缩机制冷, 急冷式 By compressor
● 出水流量 Outlet Water Volume	≈10ml/s
● 制冷温度 Cooling Temperature	进水温度25°C出水温度4°C, 进水温度40°C出水温度8°C Water Outlet volume detection, Water outlet temperature detection, Cooling temperature detection
● 计量方式 Measuring Method	流量计 Flow meter
● 单次出水量 Releasing Volume/Time	最小出水量10ml, 最大出水量500ml Min≥10ml, Max≤500ml
● 制冷剂 Refrigerant	R404
● 功能检测 Function Detection	出水流量检测, 出水温度检测, 制冷温度检测 Water Outlet volume detectionioin, Water outlet temperature detection, Cooling temperature detection
● 使用环境 Application Environment	相对湿度≤ 90%RH, 环境温度≤40°C, 海拔高度≤1000m Relative Humidity ≤ 90%RH, Environment Temperature: 4-38°C, Altitude≤1000m

Snacks Machine Parameter 售货机部分参数

最大货物尺寸 Max Good Size (mm)		单货道 Single Cargo Road				双货道 Double Cargo Road			
		4Slot 4格	5Slot 5格	8Slot 8格	12Slot 12格	4Slot 4格	5Slot 5格	8Slot 8格	12Slot 12格
L		105	85	55	37	105	85	55	37
W		75				150			
H		高度可调 Height adjustable							
货物摆放量 Goods Capacity		6层货盘 x 货盘格货道=48种货物, 具体规格可预定 6 Layers x Slot quantity x Cargo Road quantity(Customization available)							
电压 Rated Voltage		220V/50Hz 或 110V/60Hz							
功率 Power Rate		开制冷: 350W, 停制冷: 50W, 日耗电量: 6kwh Working mode:350W,Standby mode:50W,Daily power comsuption: 6kWh							

