

DoGain

High Power Diode Lasers Bars, 1064 nm, 100W CW

1064nm 100W 高功率巴条激光芯片


DG-UMB-50-47-1064-TE-100-1.5

性能参数 Performance Parameters	符号 Symbol	最小值 Minimum	典型值 Typical	最大值 Maximum	单位 Unit
Operation					
输出功率 Optical output power	Po	100			W
中心波长 Wavelength (cw)	λ_c	1050	1060	1070	nm
工作模式 Operation mode			CW		
Geometrical					
发光单元数 Number of Emitters			47		
发光区宽度 Emission region width	E.W.	90	95	100	μm
发光点周期 Emitter Pitch	P	200			μm
填充因子 Filling Factor	F	50			%
巴条长度 Bar Width	B	9800	10000	10200	μm
腔长 Cavity length	L	1480	1500	1520	μm
厚度 Thickness	D	105	115	125	μm
Electro Optical Data					
电光转换效率 Electro-optic conversion efficiency	η_c	61	66		%
斜率效率 Slope efficiency	SE	1.00	1.10		W/A
阈值电流 Threshold current	Ith	9	10		A
工作电流 Operating current	Iop	100	110		A
工作电压 Operating voltage	Vop	1.5	1.6		V
光谱宽度 (FWHM) Spectral width	$\Delta\lambda$	3.5	4.5		nm
波长温度系数 Wavelength tuning vs. temperature	$\Delta\lambda/\Delta T$	0.3			nm/°C
垂直远场发散角 (FWHM) Vertical F.F. divergence angle	θ_{\perp}	35			Deg
水平远场发散角 (FWHM) Horizontal F.F. divergence angle	$\theta_{//}$	7			Deg

备注：本参数为产品进行MCC封装，CW电流模式，导热板25°C下条件下的测试参数。

Note: These parameters were obtained by testing MCC packaged products in the CW mode at 25°C.

◆ Power-Current-Voltage-Efficiency



◆ Spectral characteristics

