

# DoGain

High Power Diode Lasers Bars, 940 nm, 500W QCW

940nm 500W 高功率巴条激光芯片


DG-UMB-75-62-940-TE-500-2.0

性能参数 Performance Parameters	符号 Symbol	最小值 Minimum	典型值 Typical	最大值 Maximum	单位 Unit
<b>Operation</b>					
输出功率 Optical output power	Po	500			W
中心波长 Wavelength (cw)	$\lambda_c$	937	940	943	nm
工作模式 Operation mode			QCW		
<b>Geometrical</b>					
发光单元数 Number of Emitters		62			
发光区宽度 Emission region width	E.W.	109	114	119	μm
发光点周期 Emitter Pitch	P		150		μm
填充因子 Filling Factor	F		75		%
巴条长度 Bar Width	B	9800	10000	10200	μm
腔长 Cavity length	L	1980	2000	2020	μm
厚度 Thickness	D	105	115	125	μm
<b>Electro Optical Data</b>					
电光转换效率 Electro-optic conversion efficiency	$\eta_c$	55	60		%
斜率效率 Slope efficiency	SE	1.2	1.2		W/A
阈值电流 Threshold current	Ith		35	40	A
工作电流 Operating current	Iop		450	500	A
工作电压 Operating voltage	Vop		1.8	2.0	V
光谱宽度 (FWHM) Spectral width	$\Delta\lambda$		4	5	nm
波长温度系数 Wavelength tuning vs. temperature	$\Delta\lambda/\Delta T$		0.3		nm/°C
脉冲宽度 Pulse Width	$\tau$		400		μs
脉冲频率 Pulse frequency	f		200		Hz
脉冲占空比 Pulse duty cycle			8		%
垂直远场发散角 (FWHM) Vertical F.F. divergence angle	$\theta_{\perp}$		/		Deg
水平远场发散角 (FWHM) Horizontal F.F. divergence angle	$\theta_{//}$		/		Deg

备注：本参数为产品进行MCC封装，QCW电流模式，导热板25°C下条件下的测试参数。

Note: These parameters were obtained by testing MCC packaged products in the QCW mode at 25°C.

◎ Power-Current-Voltage-Efficiency



◎ Spectral characteristics

