

## Technical Data Sheet

<b>Silicone BME-2410</b>	
<b>Description</b>	
BME-2410 shows a good slip and excellent anti-crater properties. It is highly effective and can be used in a broad range of different coatings and inks.	
<b>Technical Data</b>	
Appearance	clear liquid
Active matter content, %	100
Chemical	Polyether siloxane co-polymer
Solvent	Solvent free
<b>Application</b>	
As supplied calculated on total formulation: 0.05 - 1.0 % Suit for: Wood coatings, General industrial coatings, Architectural paints, Printing Inks	
Anti-crater effect	+ + + + +
Flow promotion	+ + + + -
Slip effect	+ + + + +
Anti-blocking	+ + + + -
Low foam	+ - - - -
<b>Suitability</b>	
Waterborne <input checked="" type="checkbox"/>	Solventborne <input checked="" type="checkbox"/>
2-pack 100% <input checked="" type="checkbox"/>	Radiation-curing <input checked="" type="checkbox"/>
Pigmented coatings <input checked="" type="checkbox"/>	Clear coatings <input checked="" type="checkbox"/>
<input checked="" type="checkbox"/> not suitable <input checked="" type="checkbox"/> partly suitable <input checked="" type="checkbox"/> suitable	
<b>Key Benefits</b>	
<ul style="list-style-type: none"> <li>✓ excellent slip effect</li> <li>✓ excellent anti-crater effect</li> <li>✓ improves leveling properties</li> </ul>	
<b>PROCESSING INSTRUCTIONS</b>	
<ul style="list-style-type: none"> <li>✓ Addition to the coating as supplied or as a pre-dilution is possible.</li> <li>✓ Pre-dilution in a suitable solvent simplifies dosage and incorporation.</li> </ul>	
<b>Storage information</b>	
When stored in an original unopened packaging between +4 and +40°C, the product has a shelf life of at least 60 months from the date of manufacture.	
<b>Producer information</b>	
SHANGHAI TITANOS INDUSTRY CO.,LTD. ADD: ROOM 2101. NO. 915 ZHENBEI ROAD, SHANGHAI 200333, P.R. OF CHINA. TEL: +86-21-32513559/32513560 FAX:+86-21-32513556 E-mail: sales@titanos.com.cn	