

Wetting agent Wet-5348	
Description	
<p>Wet-5348 is a special designed silicone coating additive. Wet-5348 can used in aqueous coatings, adhesives, printing inks, overprint varnishes and care products with a strong reduction of surface tension and therefore an improvement of substrate wetting. Does not increase the surface slip. Suitable for systems that do not contain co-solvents.</p>	
Technical Data	
Appearance	Light brown liquid
Active matter content,%	100%
Chemical	Polyether-modified siloxane
Solvent	N/A
Application	
<p>Wet-5348 can used in aqueous coatings, solvent borne coatings, showing high performance wetting in substract like plastic and wood. As supplied calculated on total formulation: 0.05 - 0.5 % Wet-5348 may be added during any stage of prodcuton, but is preferably added to the finished formulation.</p>	
Key Benefits	
<ul style="list-style-type: none"> ✓ Good Wetting performance ✓ Significant decrease in the surface tension of aqueous systems and therefore particularly improves substrate wetting and leveling ✓ Suitable for substrate usually difficult to wet like plastic and wood. 	
Storage information	
<p>Product has a shelf life of 24 months from the date of delivery and under the condition, that it is stored in factory-packed containers and protected against extreme weather conditions, particularly against heat and cold. The optimum storage temperature is in between 5°C and 40°C.</p>	
Producer information	
<p>SHANGHAI TITANOS INDUSTRY CO.,LTD. ADD:ROOM 2101.NO. 915 ZHENBEI ROAD, SHANGHAI 200333,P.R.OF CHINA. TEL:+86-21-32513559/32513560 FAX:+86-21-32513556 E-mail: sales@titanos.com.cn</p>	