

Company Profile 公司简介

中山川崎机械科技有限公司是一家专业从事设计制造液态硅胶送料机、液态硅胶发泡机及成型自动化设备的公司,为客户提供液态硅胶产品的一体化、智能化解决方案。总部位于中国广东省中山市。

川崎所有设备均为自主研发,有独立知识产权,广泛应用于医疗、3C、日用品、婴童、汽车、电力等领域。有多种个性化方案供客户选择,操作简易,生产效率高,省电节能,配比精度和重复精度高。尤其擅长大流量输送、精确计量、色浆添加、定做设计等。

Zhongshan Research Mechanical Technology Co.,ltd is a company specializing in the design and manufacture of LSR dosing machine, LSR foaming machine and molding automation equipment, and provides customers with integrated and intelligent solutions for LSR products. The headquarters is located in Zhongshan City, Guangdong Province, China.

All of Research equipment is independently developed with independent intellectual property rights, and is widely used in medical, 3C, daily use, baby products, automobile, power field and other fields. There are a variety of personalized solutions for customers to choose, easy to operate, high production efficiency, power saving and energy saving, high ratio accuracy and repeatability. Research is especially good at large-flow dosing, accurate metering, pigment addition, special customized design, etc.

D521

液态硅胶送料机



中山川崎机械科技有限公司

ZHONGSHAN RESEARCH MECHANICAL TECHNOLOGY CO.,LTD.

地址：广东省中山市民众镇接福路139号A栋

ADD：Building A, No.139, Jiefu Road,Minzhong Town,Zhongshan, Guangdong Province

Tel：0760-88962007

Fax：0760-85529957

website：www.zsresearch.cn



中山川崎机械科技有限公司

ZHONGSHAN RESEARCH MECHANICAL TECHNOLOGY CO.,LTD

■ 技术规格

Technical Specifications

项目 Item	类型 Type	参数 Parameter
胶料粘度 Material viscosity	旋转粘度 Rotary viscosity	0-3000000mpa.s
料桶 Drum	液态硅胶标准桶 Standard package	20/200L
配比精度 Mixing precision	自动校正平衡 Automatically balanced	1%
气源压力 Air supply	—	0.6-0.8Mpa
理论出胶速度(静态混合器出口) Output speed in theory(outlet of static mixer)	气动 Pneumatic	0-1000g/min
储料容积 Charging volume	气动 Pneumatic	0-250g (A+B)
最大空气消耗量 Max. air consuming	—	5 Ft^3/min
额定总功率 Rated total power	—	0.3Kw
重量 Weight	—	0.8t
主机外形尺寸 Dimension (L×W×H)	—	1200×1200×2000(mm)

本公司产品不断研发设计致规格有所变更时, 恕不另行通知。
Due to continual improvements, specifications are subject to change without notice.

D521液态硅胶送料机技术特点

Feature of D521

- 1

全气动的二次计量系统, 节能清洁。
Pneumatic secondary metering system, energy saving and clean.
- 2

AB胶闭环自动校正平衡。
Closed loop control system, adjust A&B balance automatically.

- 3

对剩余胶料、压力等参数进行数字化监测并自动校正, 保证配比更为精确。
The remaining material, pressure and other parameters are digitally monitored and automatically corrected to ensure a more accurate proportion.

- 4

色浆第三剂添加, 添加量可调节, 混色均匀, 重复精度高。
Pigment is third additive, the addition amount is adjustable, the color mixing is uniform, and the repeatability is high.

- 5

专利截止阀、气动射嘴。
Patent cut-off valve, pneumatic nozzle.

