



	PIN	1	2	3	4
1	COM1	COM1			
2	COM2		COM2		
3	COM3			COM3	
4	COM4				COM4
5	SEG1	1A	1F	1E	1D
6	SEG2	P2	1B	1G	1C
7	SEG3	2A	2F	2E	2D
8	SEG4	P1	2B	2G	2C
9	SEG5	3A	3F	3E	3D
10	SEG6	P3	3B	3G	3C
11	SEG7	4A	4F	4E	4D
12	SEG8	P4	4B	4G	4C



大连奇耘电子有限公司
DALIAN QIYUN DISPLAY CO., LTD.

确认此型号所有图纸;签字确认:

DESIGNED BY: ZN	GDC04557R(P)-12	VERSION: 2.0 NO. 1 OF 3	1. DISPLAY TYPE: TN/POSITIVE	6. POLARIZER TYPE: REFLECTIVE	VERSION	REVISION RECORD
CHECKED BY: HQM		UNIT: mm DATE: 2015-10-20	2. OPERATING VOLTAGE: 3.0V	7. VIEWING DIRECTION: 6:00	1.0	初版
TOLERANCES UNLESS OTHERWISE SPECIFIED: ± 0.2			3. DRIVE MODE: 1/4D, 1/3B	8. CONNECTOR: PIN	2.0	1 1 版改尺寸
			4. OPERATING TEMP: $0^\circ\text{C} \sim 60^\circ\text{C}$	9. CUSTOMER NO:	3.0	
			5. STORAGE TEMP: $-10^\circ\text{C} \sim 70^\circ\text{C}$	10. LCM NO:	4.0	



大连奇耘电子有限公司
DALIAN QIYUN DISPLAY CO., LTD.

DESIGNED BY:

ZN


GDC04557R(P)-12

VERSION: 2.0

NO. 2 OF 3

CHECKED BY:

HQM



UNIT: mm



DATE: 2015-10-20

TOLERANCES UNLESS OTHERWISE SPECIFIED: ± 0.2

全显示效果图

SEG

COM



大连奇耘电子有限公司
DALIAN QIYUN DISPLAY CO., LTD.

DESIGNED BY:

ZN


GDC04557R(P)-12

VERSION: 2.0

NO. 3 OF 3

CHECKED BY:

HQM



UNIT: mm

DATE: 2015-10-20

TOLERANCES UNLESS OTHERWISE SPECIFIED: ± 0.2

此页图案仅供走线参考!