

Pistons

Hongyang's pistons are made to exact tolerances and include a variety of extended wear materials yielding excellent service life. Piston has single action, double action, single action vulcanization and double action vulcanization piston ,which has A, K, B & L type. Outer round is determined based on the liner bore, it has 3" to 8" and piston has 1"、1-1/2"、1-5/8". Metric size it has 100mm to 220mm.

Assemble pistons it has Buna-N Rubber and Urethane



Bonded pistons it has Urethane and Polyurethane. Has Dual Duro and Dual-Hardness Patriot style.



Double action piston has
API-1# 3"~5"
API-3# 3"~7.5"
API-4# 4.5"~8"
API-5# 4.5"~8"
API-6# 5"~8"



Package of Piston Assembly
With its Sleeve & Seal



Other special material of piston, suitable for high temperature resistant, low temperature resistant, high pressure resistance, oil resistance, etc.



Piston Replacement Rubbers
Piston Rubber Kit
Buna-N Rubber
Polyurethane Rubber



JINAN HONGYANG PETROLEUM MACHINERY CO., LTD.

Add: Xunyucun North, Dongjia Town, Licheng District, Jinan City, Shandong China

www.pumppartssupplier.com

Tel:+86-531-82687338

hyoiking@aliyun.com

Fax: +86-531-82687336

Piston Hub, the material used is ASTM5140. the premium forged steel. heat treatment process and CNC machined to meet the requirements of the standard.



Plate & Snap Ring, Plate material used is ASTM1020 steel, Material of snap used is ASTM1066 steel. it is divided into A、K、B、L type.

