

1, Download firmware file, and un-zip it to get two files: 273.BRN and FY_KEY. And save in an empty Micro SD card.

2, Before you update new firmware, please check the old firmware version firstly: Setting – System – System information, and write down the version.

3, Power off device, then insert micro sd card, and power on device. The screen will appear you “FW ISP”, it means device is updating. When updating finished, screen will become black. Please power off and power on device again, and check firmware version again. If it has been changed, it means updating is successful.

4, On download link, we often offer standard firmware only, and please find out the model number as same as you bought. And for other inquiry, please go to FAQ to look for the answers or send us mail.

5, For different model number products, maybe different firmware file name, such as 273.BRN for ezcap273, and 274.BRN for ezcap274, please don't care, just copy them to micro sd card.

1, 下载固件程序，解压缩并得到两个文件：273.BRN 和 FY_KEY。将其保存在空白的 TF 卡中。

2, 在正式升级前，请先确认旧的固件程序版本：设置 – 系统 – 系统信息，然后记下旧固件版本信息。

3, 关闭设备电源, 插入 TF 卡到设备, 再启动设备电源. 显示屏会出现"FW ISP"字样, 表示设备正在升级固件程序。等到显示屏变黑则表示升级完成, 此时关闭电源再重启电源, 然后再次去确认固件程序版本, 如果和之前的改变了, 则表示升级成功。

4, 网站下载链接我们通常仅仅会提供标准固件程序, 请你确认你购买的具体型号并找到它。如果你需要其它特别的需求, 请在对应的常见问题链接去寻找答案, 或直接给我们写邮件。

5, 不同型号的产品可能会有不同的固件文件名称, 比如 ezcap273 是 273.BRN, ezcap274 是 274.BRN。所以无需在意, 直接将解压缩的文件拷贝到 TF 卡即可。