



Product features:

1. User friendly Control panel
2. Anti-static (ESD) Ionizer bar on outlet (optional for inlet)
3. Easy adhesive rolls replacement
4. Pre-warning function to replace adhesive roll
5. Selectable number of cleaning cycle per adhesive sheet
6. Running modes: clean or bypass
7. width adjustment (via leadscrew)
8. ESD value measurement on outlet (optional)
9. Automatic width adjustment (optional)
10. ESD coating (optional)
11. IPC-HERMES--9852, IPC-CFX (optional)
12. Tower lamp and buzzer
13. SPC interface

Technical Specifications

No	Item	Design Parameter
1	Machine dimension [L*W*H]	600mm*950mm*1950mm
2	Power supply	AC220V/50/60HZ
3	PCB transport height	910±20mm
4	PCB size [L-W]	50mm*50mm-400mm*460mm
5	PCB thickness	0.4-5mm
6	Air pressure	4-6bar
7	Conveyor width adjustment mode	Automatic
8	Cleaning side	Single-sided cleaning + straight-through
9	Cleaning system	Brush cleaning + vacuuming + sticky dust + static removal
10	Sticky roller	2 imported ESD silicone
11	Static eliminator	SMC
12	PCB transport direction	Left to Right or Right to Left (optional)
13	Sticky paper replacement	drawer-type
14	Control system	PLC+Screen

(*Also customized for other special requirements)