



## MAIN FEATURES

7" touch screen LCD

6 temperature measurement and power output channels

PID control algorithm with auto tuning function

Two work modes: temperature mode and voltage mode

Remote control and diagnosis

Communication Interface: USB/Ethernet

Easy firmware upgrade



Front Panel



Rear Panel

## TECHNICAL DATA

Output Voltage	0~220V
Output Current	6×16A (Max)
Output Power	20kW (Max)
Thermocouple	Type K
Output Channel	6 channels, parallel
Work Mode	CV (constant voltage) / PID control
Remote Control	Ethernet
Power Distribution	Three-phase AC (3L + N), 380V/32A
Dimension	480×420×178mm
Weight	7.2kg

## MAIN APPLICATIONS


Chamber baking

Furnace baking

Pipeline heating

Electric Stove

## Part Number Composition



Scan & Follow

**ACME (Beijing) Technology Co., Ltd**

Address: 2<sup>nd</sup> Floor, Building #7, No.11 Xingke East Street,  
Yanqi Economic Development Zone, Huairou District,  
Beijing 101407, China

Website: [www.acme-bj.com](http://www.acme-bj.com)

E-mail: [service@acme-bj.com](mailto:service@acme-bj.com)/[sales@acme-bj.com](mailto:sales@acme-bj.com)

Phone: 4000003370