

## Ti-40 Automatic Potential Titrator



### FEATURES

- LCD display screen and smart guide system.
- Titration methods, curves and results are displayed in detail.
- Replaceable burette with high-accuracy (10 ml or 20 ml selectable).
- Support titration modes: DET (dynamic equivalence point titration), MET (monotone equivalence point titration), SET (Preset Endpoint Titration) and MAT (manual titration).
- pH calibration and measurement are supported.
- Store up to 50 titration data sets (GLP-compliant) and 1 latest set of titration curve.
- Data can be easily transferred to printer via RS-232 communication interface..
- Titrator can be controlled by computer via USB or RS-232 communication interface.

Model		Ti-40
Burette	Repeatability	0.2%
	Accuracy	10ml Burette: $\pm 0.025\text{ml}$ 20ml Burette: $\pm 0.035\text{ml}$
Mechanical Unit	Resolution	1/14000
Measuring Unit	Range	(-1800.0~1800.0) mV (0.00~14.00)pH
	Resolutions	0.1mV, 0.01pH
	Accuracy	pH: $\pm 0.01\text{pH}$ mV: $\pm 0.05\%\text{FS}$
	Fluctuation	$\pm 0.3\text{mV}/3\text{h}$
Temp. Compensation	Range	(-5.0~105.0) °C
	Resolutions	0.1 °C
	Accuracy	$\pm 0.3$ °C
General	Power Supply	AC Adapter, 100-240V AC input, C24V output
	Dimensions	340×400×400 mm
	Weight	10 kg